

CS 311: Computational Structures

Problem Set 5

James Hook

Prepared: November 3, 2015

1. This problem is based on Sipser 2.22.

In the development of the problem below, I introduce the notation $x.i$ for the i th character of string x . I did not specify if this is 0 based or 1 based; you may use either convention provided you are consistent. If x is the string 0110 then the 0-based interpretation would be that $x.0 = 0$, $x.1 = 1$, $x.2 = 1$ and $x.3 = 0$.

- (a) Show that the language $A = \{x\#y \mid |x| \neq |y|\}$ is context free. (That is, strings of different lengths.)
 - (b) Show that the language $B = \{x\#y \mid x.i = 0 \wedge y.i = 1 \text{ for some position } i\}$ is context free, where $x.i$ is the i th symbol of x .
 - (c) Show that $\{x\#y \mid x \neq y\} = A \cup B \cup C$, where $C = \{x\#y \mid x.i = 1 \wedge y.i = 0 \text{ for some position } i\}$.
 - (d) Conclude $D = \{x\#y \mid x \neq y\}$ is a context free language.
 - (e) Observe that $\bar{D} \cap (0 \cup 1)^* \# (0 \cup 1)^* = \{x\#y \mid x = y\}$, a language known to not be context free. Discuss why this is evidence that the Context Free Languages are not closed under complement.
2. Sipser 2.26 [Counting argument related to pumping]
 3. Sipser 2.30 (a) [Context Free Language Pumping Lemma application]
 4. Sipser 2.30 (d) [Context Free Language Pumping Lemma application]