CS 410/584, Algorithm Design & Analysis, Lecture Notes 8

Computational Geometry

Algorithms for manipulation of geometric objects

We will concentrate on 2-D geometry

Numerically robust – try to avoid division
- Round-off error
- Divide-by-0 checks

Techniques
Sweep
Angle Scan
Divide + Conquer

Basics

Point p = (x,y)

Line segment p_1–p_2

Can represent different things



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Relative Orientation of Segments



How do we know which case it is?

Could compare slopes

$\frac{x1}{y2} > \frac{x2}{y2}$

But that has division problems

Cross Product

Can compare slopes without division

y1/x1 < y2/x2

x2·y1 < x1·y2

0 < x1·y2 − x2·y1

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Examples

$x1 \cdot y2 - x2 \cdot y1$



$(3,2)\times(2,4)=$ $12-4=8$

$(3,2)\times(4,1)=$ $3-8=-5$

$(3,2)\times(2,-2)=$ $-6-4=-10$

$(3,2)\times(-3,1)=$ $3-(-6)=9$

$(3,2)\times(-6,-4)=$ $-12-(-12)=0$

Left Turn, Right Turn

How do we know if a sequence of two line segments turns to left or right?



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Use Cross Product

Translate p2 to origin, along with other points. Look at relative position of p1, p3



Intersection: Cases



Main conditions

p1, p2 on different sides of p3-p4
p3, p4 on different sides of p1-p2

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

How Do You Tell Different Sides?

One is a left turn and one is a right turn



If 0 Change in Direction

Then the point is on the p1—p2 line somewhere

p3 on the p1–p2 line

(x1,y1) (x2,y2) (x3,y3)

```
OnSegment(p1,p2,p3)
1. min(x1,x2) ≤ x3 ≤ max(x1,x2)
2. min(y1,y2) ≤ y3 ≤ max(y1,y2)
```



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Beware of Boundary Conditions

- Co-linear points, points on line
- Multiple intersections

- Vertical, horizontal lines
- p1—p2 versus p2—p1
- Degenerate objects

  What about intersection with the degenerate line segment p3—p3

Polygon

Polygon – closed sequence of sides

Simple polygon if edges don't cross





© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Exercise 33.1-7

Find out if point p is in simple polygon P
P has n points p1, p2, …, pn, want O(n)

1. Assume no 3 consecutive points on the same line
2. Make sure p doesn't lie on any edge of P
   Call Intersect (p_i, p_{i+1}) & (p p) O(n)
3. Construct a segment p—q where q is for sure outside of P
4. Count number of segments of P that intersect p—q
   even # = outside
   odd # = inside

How to Find a Point Outside of P

Let x′ = max xi
If p = (x, y), let q = (x'+1, y)



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Cases to Watch out For

p—q passes through a vertex



What's the Difference in These Cases

Do previous and next points lie on the same side of p—q or not?



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

In Cases III & IV, need to test if p_{i-1} and p_{i+2} are same side of p—q or not

In O(n) time, can head around polygon, counting number of intersections with p—q, taking into account cases I-IV

Pairwise Intersection

Have a collection of *n* line segments, want to know if there is a pair that intersect

- Perhaps they represent traces on a circuit layer

Sweep = A vertical line moving left to right over the segments (conceptually)

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Interested in Intersections with Sweep Line

Want the intersection points in top-to-bottom order



Intersecting Segments

Intersecting segments adjacent in some sweep list

Assumptions:
- No 3 segments intersect
- No vertical segments



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Where Does Sweep List Change?

Sweep list changes at segment endpoints.

Update sweep list "just after" encountering each endpoint

- after it enters for left endpoint
- after it leaves for right endpoint



Maintaining Sweep List

Keep sweep list as a structure that supports O(log n) operations red-black tree

Operations:

- Insert segment
- Delete segment
- Above: find the segment above the most recent change
- Below: find the segment below the most recent change

Some kind of balanced tree, ordered on y-value of the intersection with the sweep line

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

How to Order New Segment on Sweep Line

Need to know where new segment B is relative to each segment A already in sweep line.



Order Endpoint List

Need to have the endpoints in the order that the sweep line encounters them

Sort on x-coordinate $O(n \lg n)$

What about ties?

- Left endpoints win over right endpoints
- Lower y-coordinate wins over higher y-coordinate



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Algorithm

EP (endpoints): sorted as described

SL (sweep list)

```
for each p in EP in order
```

p is the left endpoint of segment s

- insert s into SL
- check if s intersects lines above and below

O(lg n)

p is right endpoint of s

- check if segments above and below s intersect each other (stop if intersection reported)
- delete s from SL

O(lg n)

Example



EP	SL	
aL	A	
bL	A, B	check(A,B)
cL	C, A, B	check(C,A)
aR	C, B	check(C,B)
dL	C, B, D	check(D,B)
bR	C, D	check(C,D) ✓
dR		
aR		

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Polar Angle

Next couple algorithms, need to order points by polar angle.



Discussion Problems

Have Q = {p1, p2, …, pn}

1. Given p, find point pi in Q with smallest positive polar angle from p.
2. Sort points in Q by increasing polar angle from x axis.

Try to solve these problems using only cross product.

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Convex Hull

Given Q = {p1, p2, …, pn}, what is smallest convex polygon P such that every point is in or on P

Vertices of P will be in Q

Consider Q with 100 points.

- What is the most that can be on convex hull?
- What is the fewest that can be on convex hull?

Uses of Convex Hull

Approximate more complicated shape by convex hull, for intersection "pre-check"



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Multiple Convex Hull Algorithms

Some algorithms are good when the number of points on the hull is low. Others perform same on any number of points.

Can often use heuristics to speed up either.

Make any convex polygon R using points in Q. Then points on interior of R are not on convex hull



One Way to Choose R

Let pa, pb, pc, pd be the points with min x, max x, min y, max y.

Let R be polygon pa—pd—pb—pc—pa

Will this always remove points?



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Jarvis's March

Package wrapping:

Of points not on hull so far, which is at least angle with the last point on the hull



Issues

Co-linear points: What if several points on same edge of convex hull?

Want most points: pick closest to add next

Want least points: pick farthest

How to find distance?

$(x_1 - x_2)^2 + (y_1 - y_2)^2$



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Issues, Continued

Where to start:

Min y coordinate
(if several, then, max x coord among them)

What line to use through first point:

Horizontal line through first point



Complexity

At each point, do an O(n) process to find point with minimum positive polar angle.

How many times do we need to do that search?

Number of points on the hull

So, O(n·h) where h = # of points on hull

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Graham Scan

Start with "angle sweep" and remove points

- Find point p0 with minimum y-coordinate
- Sort points by polar angle from horizontal line through p0
- Always O(n log n), no matter how many points on hull



Candidate Hull on Stack

Push points on stack in order

- Before you push, check angle with top two points on stack

Left turn:



Right turn:



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

May be Several Pops in a Row

Can have several points popped because of pi



Graham Scan: Start-up

```
Input:  set of points  p[0..n]
1. Let p[0] have  min y coord (min x if ties)
2. sort p[1]...p[n] by angle
   with  horizontal line through p[0]
3. Have stack S
4. Push( p[0] )
   Push( p[1] )
   Push( p[2] )
```


© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Graham Scan: Body

```
for i = 3 to N
  while NEXT-TO-TOP—TOP—p[i] is
      is a right turn
    POP (TOP)
  PUSH( p[i] )
S holds the convex hull when done
```

stack

Complexity

(Time complexity over all)

O(n log n) to sort points

O(n) for rest

- Each point gets pushed once — O(n) pushes total
- Can do multiple pops in while-loop, but each is of a previously pushed point

#pops < #pushes

O(n) pops total

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Planar Minimal Spanning Tree

Suppose I give you points in the plane to represent nodes in a graph

- All edges exist, weight is distance between end points.
- What is the first edge to add?



Closest Pair

Use divide and conquer

Split points in half by x-coordinate

- Find closest pair on each side
- Let δ = $\min(\delta_1, \delta_2)$



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Closer Pair

Can there be a pair of points closer than δ?

Yes! Near the boundary

So check all points within $\pm\delta$ of dividing line



Avoid Too Many Comparisons

Don't want to compare all pairs of points near the boundary, otherwise get $O(n^2)$

Only compare each point near boundary to next 7 in order of y-coordinate



© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier

Complexity

Initial $O(n \log n)$ work for x-sort + y-sort

For n points, have two sub-problems of size n/2

How much other work outside of the recursive calls?

- Might seem like O(n lg n) because of the sorting
- That would give complexity $O(n(\lg n)^2)$

However, make two lists of the points at the very beginning, one sorted on x and the other on y

- Can construct ordered lists for sub-problems in linear time.
- $T(n) = 2T(n/2) + O(n)$ $O(n \log n)$

© 1994, 2003, 2003, 2006, 2008, 2009, 2011 David Maier